CHASSIS COMPARISON - FREIGHTLINER® S2RV VERSUS M2 106



S2RV Chassis



M2 106 Chassis

6.7L ISB Cummins® Turbo Diesel (Parent Bore – Throw Away)	ENGINE	8.9L ISL Cummins® Turbo Diesel (Wet Sleeve – Rebuildable)
360 HP (at 2,600 RPM)	HORSEPOWER	350 HP (at 2,000 RPM)
800 LB/FT (at 1,800 RPM)	TORQUE	1,000 LB/FT (at 1,400 RPM)
3000 MH Allison® 6-Speed Electronic Push-Button	TRANSMISSION	3200 TRV Allison® 6-Speed Electronic Push-Button
185 Amps	ALTERNATOR	275 Amps
12,000-LB Hitch	HITCH SIZE	20,000-LB Hitch
Low Cab	CAB HEIGHT	High Cab (4.7" Higher)
Four (4) Alcoa® Aluminum Wheels (Rear Inner Wheels = Steel)	WHEELS	Six (6) Alcoa® Aluminum Wheels
Factory SACH® Shocks	FRONT SHOCKS	Upgraded Bilstein® Gas-Charged Shocks
Rear	SWAY BAR	Front
Cummins® VG Engine Brake with Dash Switch	AUXILIARY BRAKING SYSTEM	Dual-Stage C-Brake by Jacobs® with High/Off/Low Braking Dash Switch
N/A	REAR LOCKING DIFFERENTIAL	EQUIPPED
N/A	REAR AIR SUSPENSION DUMP SWITCH ON DASH	EQUIPPED
N/A	QUICK DISCONNECT FITTING WITH TIRE INFLATION KIT	EQUIPPED
100-Gallon Rear Steel Tank	FUEL CAPACITY	100-Gallon Aluminum Front Saddle Tanks
10-Gallon Tank under Cab	D.E.F. CAPACITY	6-Gallon Tank Behind Cab
Three (3)-Years / 50,000-Miles	CHASSIS WARRANTY	Two (2)-Years / Unlimited Miles
Five (5)-Years / 100,000-Miles	POWERTRAIN WARRANTY	Five (5)-Years / 100,000-Miles