




1217 E. 7th Street
Mishawaka, IN 46544
Phone: 1-800-334-4712
1-888-339-2539
Fax: 574-256-6743

T.I.P. Troubleshooting Information on Power Gear


HOW TO 'LEVEL' THE BUBBLE LEVEL

SYSTEMS PRODUCED 1991-2000



- 1) Level the coach utilizing the power gear leveling system by placing a torpedo or carpenters level on a permanent surface in the galley, such as, the refrigerator, stove or countertop.
- 2) Level the coach until the torpedo or carpenters level in the galley indicates level front to back and left to right.
- 3) Loosen mounting screws that secure two way level, located the drivers area, that is used with the power gear leveling system control pad.
- 4) Add or remove shims between bubble level and mounting surface until bubble level indicates level front to back and left to right, Then secure the bubble level with screws.
- 5) Retract all jacks

SYSTEMS PRODUCED 2000 - Present



- 1) Level the coach utilizing the power gear leveling system by placing a torpedo or carpenters level on a permanent surface in the galley, such as, the refrigerator, stove or countertop.
- 2) Level the coach until the torpedo or carpenters level in the galley indicates level front to back and left to right.
- 3) Loosen mounting screws that secure round level, located in the drivers area, that is used with the power gear leveling system control pad.
- 4) Tighten or loosen the three screws until bubble is centered in the circle printed on the level.
- 5) Retract all jacks